

Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN

Common features of Zytel® nylon resin include mechanical and physical properties such as high mechanical strength, excellent balance of stiffness and toughness, good high temperature performance, good electrical and flammability properties, good abrasion and chemical resistance. In addition, Zytel® nylon resins are available in different modified and reinforced grades to create a wide range of products with tailored properties for specific processes and end-uses. Zytel® nylon resin, including most flame retardant grades, offer the ability to be coloured.

The good melt stability of Zytel® nylon resin normally enables the recycling of properly handled production waste. If recycling is not possible, we recommend, as the preferred option, incineration with energy recovery (-31kJ/g of base polymer) in appropriately equipped installations. For disposal, local regulations have to be observed.

Zytel® nylon resin typically is used in demanding applications in the automotive, furniture, domestic appliances, sporting goods and construction industry.

Zytel® 70G30HSLR ECO-R 312 BK099 is a 30% glass fibre reinforced, heat stabilised, hydrolysis resistant polyamide 66 resin for injection molding. It has same performance and processing properties as Zytel® 70G30HSLR BK099.

Zytel® 70G30HSLR ECO-R 312 BK099 incorporates 30% post-industrial recycled content (PIR) by weight in the finished product through mass balance allocation. The product is a drop-in replacement to the standard grade with the same performance and processing properties and contributes to the displacement of virgin fossil resources. The recycled source and allocated content in the product are certified according to ISCC PLUS mass balance approach.

Rheological properties

	dry/cond.		
Viscosity number	4150 ^{[1]*/}	in ³ /lb	ISO 307, 1628
Molding shrinkage, parallel	0.3 / -	%	ISO 294-4, 2577
Molding shrinkage, normal	1.0 / -	%	ISO 294-4, 2577
Melt viscosity , @ 1000 sec-1, 280 °C	1900 / *	P	ISO 11443

[1]: acid sulphuric 96%

Typical mechanical properties

	dry/cond.		
Tensile modulus	1.45E6 / 1.02E6	psi	ISO 527-1/-2
Tensile stress at break, 5mm/min	29000 / 18900	psi	ISO 527-1/-2
Tensile strain at break, 5mm/min	3 / 5	%	ISO 527-1/-2
Flexural modulus	1.31E6 /	psi	ISO 178
[DS]			
Flexural strength	40600 / 2	psi	ISO 178
	9000 ^[DS]		
Flexural stress at 3.5%	39200 / 24700	psi	ISO 178
Charpy impact strength, 23 °C	33.3 / 38.1	ftlb/in ²	ISO 179/1eU
Charpy impact strength, -30 °C	33.3 / 33.3 ^[DS]	ftlb/in ²	ISO 179/1eU
Charpy impact strength, -40 °C	30.9 / -	ftlb/in ²	ISO 179/1eU

Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN

Charpy notched impact strength, 23 °C	5.71 / 7.14	ftlb/in ²	ISO 179/1eA
Charpy notched impact strength, -30 °C	4.28 / 4.28 ^[DS]	ftlb/in ²	ISO 179/1eA
Charpy notched impact strength, -40 °C	4.28 / 4.28	ftlb/in ²	ISO 179/1eA
Izod notched impact strength, 23 °C	4.76 / 5.71	ftlb/in ²	ISO 180/1A
Izod notched impact strength, -30 °C	4.76 / -	ftlb/in ²	ISO 180/1A
Izod notched impact strength, -40 °C	4.76 / -	ftlb/in ²	ISO 180/1A
Hardness, Rockwell, M-scale	104 / 88		ISO 2039-2
Hardness, Rockwell, R-scale	124 / 117		ISO 2039-2
Ball indentation hardness, H 961/30	39200 / 26800	psi	ISO 2039-1
Multiaxial Impact, Total Energy, 4.5m/s, 2mm	5 / -	Btu	ISO 6603-2

[DS]: Derived from similar grade

Thermal properties

	dry/cond.		
Melting temperature, 10 °C/min	504 / *	°F	ISO 11357-1/-3
Glass transition temperature, 10 °C/min	167 / 68	°F	ISO 11357-1/-3
Temperature of deflection under load, 1.8 MPa	487 / *	°F	ISO 75-1/-2
Temperature of deflection under load, 0.45 MPa	502 / *	°F	ISO 75-1/-2
Coefficient of linear thermal expansion (CLTE), parallel	0.12 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), parallel, -40-23 °C	0.144 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), parallel, 55-160 °C	0.0722 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal	0.444 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal, -40-23 °C	0.389 / *	E-4/°F	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal, 55-160 °C	0.722 / *	E-4/°F	ISO 11359-1/-2
Thermal conductivity, flow	0.36	W/(m K)	ISO 22007-2
Thermal conductivity of melt	0.21	W/(m K)	ISO 22007-2
Specific heat capacity of melt	2290	J/(kg K)	ISO 22007-4

Flammability

	dry/cond.		
Burning Behav. at 1.5mm nom. thickn.	HB / *	class	IEC 60695-11-10
Thickness tested	0.0591 / *	in	IEC 60695-11-10
Burning Behav. at thickness h	HB / *	class	IEC 60695-11-10
Thickness tested	0.0295 / *	in	IEC 60695-11-10
Oxygen index	24 / *	%	ISO 4589-1/-2
Glow Wire Flammability Index, 1.0mm	1290 / -	°F	IEC 60695-2-12
Glow Wire Flammability Index, 2.0mm	1380 / -	°F	IEC 60695-2-12
Glow Wire Flammability Index, 3.0mm	1470 / -	°F	IEC 60695-2-12
Glow Wire Ignition Temperature, 1.0mm	1340 / -	°F	IEC 60695-2-13
Glow Wire Ignition Temperature, 2.0mm	1340 / -	°F	IEC 60695-2-13
Glow Wire Ignition Temperature, 3.0mm	1430 / -	°F	IEC 60695-2-13
Glow Wire Temperature, No Flame, 3mm	1380 / -	°F	IEC 60335-1
FMVSS Class	B		ISO 3795 (FMVSS 302)
Burning rate, Thickness 1 mm	1.46 ^[2]	in/min	ISO 3795 (FMVSS 302)

[2]: Based on Zytel® 70G30HSLR BK099

Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN

Electrical properties

Volume resistivity	dry/cond.		
Surface resistivity	>1E13 / 1E9 ^[DS]	Ohm.m	IEC 62631-3-1
Electric strength	* / 1E12 ^[DS]	Ohm	IEC 62631-3-2
Comparative tracking index	965 / 813	kV/in	IEC 60243-1
	400 / -		IEC 60112

[DS]: Derived from similar grade

Physical/Other properties

Humidity absorption, 2mm	dry/cond.		
Water absorption, 2mm	1.9 / *	%	Sim. to ISO 62
Water absorption, Immersion 24h	6 / *	%	Sim. to ISO 62
Density	1.3 / *	%	Sim. to ISO 62
	0.0495 / -	lb/in ³	ISO 1183

Emissions

Odor test	5 ^[2] class	VDA 270
-----------	------------------------	---------

[2]: Based on Zytel® 70G30HSLR BK099

Injection

Drying Recommended	yes
Drying Temperature	176 °F
Drying Time, Dehumidified Dryer	2 - 4 h
Processing Moisture Content	≤0.2 %
Melt Temperature Optimum	563 °F
Min. melt temperature	545 °F
Max. melt temperature	581 °F
Max. screw tangential speed	≤0.2 m/s
Mold Temperature Optimum	212 °F
Min. mold temperature	158 °F
Max. mold temperature	248 °F
Hold pressure range	7250 - 14500 psi
Hold pressure time	0.0762 s/mil
Hold Pressure Time (h is the max. wall thickness of the part in mm)	h ² +2 s
Ejection temperature	410 °F


Characteristics

Processing	Injection Molding
Additives	Release agent
Special characteristics	Heat stabilized or stable to heat, Hydrolysis resistant
Sustainability	Recycled Content

Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Viscosity-shear rate
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Shearstress-shear rate
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Dynamic Shear modulus-temperature (dry)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Dynamic Shear modulus-temperature (cond.)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Dynamic Tensile modulus-temperature (dry)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Stress-strain (dry)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Stress-strain (cond.)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Secant modulus-strain (dry)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Secant modulus-strain (cond.)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Tensile modulus-temperature (dry)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN


Tensile modulus-temperature (cond.)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN

Tensile Fatigue, 10Hz, R=0.1 @ in (dry)
(measured on Zytel® 70G30HSLR BK099)



Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN

Chemical Media Resistance

Acids

- ✓ Acetic Acid (5% by mass), 23°C
- ✓ Citric Acid solution (10% by mass), 23°C
- ✓ Lactic Acid (10% by mass), 23°C
- ✗ Hydrochloric Acid (36% by mass), 23°C
- ✗ Nitric Acid (40% by mass), 23°C
- ✗ Sulfuric Acid (38% by mass), 23°C
- ✗ Sulfuric Acid (5% by mass), 23°C
- ✗ Chromic Acid solution (40% by mass), 23°C

Bases

- ✗ Sodium Hydroxide solution (35% by mass), 23°C
- ✓ Sodium Hydroxide solution (1% by mass), 23°C
- ✓ Ammonium Hydroxide solution (10% by mass), 23°C

Alcohols

- ✓ Isopropyl alcohol, 23°C
- ✓ Methanol, 23°C
- ✓ Ethanol, 23°C

Hydrocarbons

- ✓ n-Hexane, 23°C
- ✓ Toluene, 23°C
- ✓ iso-Octane, 23°C

Ketones

- ✓ Acetone, 23°C

Ethers

- ✓ Diethyl ether, 23°C

Mineral oils

- ✓ SAE 10W40 multigrade motor oil, 23°C
- ✓ SAE 10W40 multigrade motor oil, 130°C
- ✓ SAE 80/90 hypoid-gear oil, 130°C
- ✓ Insulating Oil, 23°C
- ✓ Motor oil OS206 304 Ref.Eng.Oil, ISP, 135°C
- ✓ Automatic hypoid-gear oil Shell Donax TX, 135°C
- ✓ Hydraulic oil Pentosin CHF 202, 125°C

Standard Fuels

- ✓ ISO 1817 Liquid 1 - E5, 60°C
- ✓ ISO 1817 Liquid 2 - M15E4, 60°C
- ✓ ISO 1817 Liquid 3 - M3E7, 60°C
- ✓ ISO 1817 Liquid 4 - M15, 60°C
- ✓ Standard fuel without alcohol (pref. ISO 1817 Liquid C), 23°C
- ✓ Standard fuel with alcohol (pref. ISO 1817 Liquid 4), 23°C
- ✓ Diesel fuel (pref. ISO 1817 Liquid F), 23°C
- ✓ Diesel fuel (pref. ISO 1817 Liquid F), 90°C
- ✓ Diesel fuel (pref. ISO 1817 Liquid F), >90°C

Zytel® 70G30HSLR ECO-R 312 BK099

NYLON RESIN

Salt solutions

- ✓ Sodium Chloride solution (10% by mass), 23 °C
- ✗ Sodium Hypochlorite solution (10% by mass), 23 °C
- ✓ Sodium Carbonate solution (20% by mass), 23 °C
- ✓ Sodium Carbonate solution (2% by mass), 23 °C
- ✗ Zinc Chloride solution (50% by mass), 23 °C

Other

- ✓ Ethyl Acetate, 23 °C
- ✗ Hydrogen peroxide, 23 °C
- ✓ DOT No. 4 Brake fluid, 130 °C
- ✓ DOT No. 4 Brake fluid, 120 °C
- ✓ Ethylene Glycol (50% by mass) in water, 108 °C
- ✓ 1% nonylphenoxy-polyethyleneoxy ethanol in water, 23 °C
- ✓ 50% Oleic acid + 50% Olive Oil, 23 °C
- ✓ Water, 23 °C
- ✓ Water, 90 °C
- ✗ Phenol solution (5% by mass), 23 °C
- ✓ Coolant Glysantin G48, 1:1 in water, 125 °C

Symbols used:

- ✓ possibly resistant
Defined as: Supplier has sufficient indication that contact with chemical can be potentially accepted under the intended use conditions and expected service life. Criteria for assessment have to be indicated (e.g. surface aspect, volume change, property change).
- ✗ not recommended - see explanation
Defined as: Not recommended for general use. However, short-term exposure under certain restricted conditions could be acceptable (e.g. fast cleaning with thorough rinsing, spills, wiping, vapor exposure).